

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (Currently Amended) An assembly for use in continuously forming a plurality of lengths of flexible noise attenuating cutting line for use in rotary vegetation trimmers comprised of at least two ~~monofilament-polymer~~ strands of monofilament bonded together in a twisted disposition, said assembly comprising: a housing having a chamber therein; a channel disposed within said housing above said chamber adapted for fluid communication with a source of molten ~~monofilament polymer material~~ for directing said ~~material~~ molten monofilament to said chamber; a breaker plate disposed in said chamber, said plate defining an inclined inner portion and a substantially planar outer portion, said inner portion directing molten ~~material~~ monofilament from said channel onto said outer portion; a plurality of extrusion dies disposed in said outer portion of said breaker plate, each of said dies defining a die hole configuration in the lower end thereof for the extrusion of at least two strands of molten ~~monofilament polymer strands~~ therethrough; and a drive assembly for rotating each of said dies at a ~~predetermined~~ speed to effect a twisting together of the molten strands of ~~polymer material~~ monofilament being extruded through each of said dies.

2. (Currently Amended) The assembly of claim 1 wherein said drive assembly is operatively connected to said dies so as to effect synchronous rotation ~~synchronously rotates~~ of each of said dies at said ~~predetermined~~ speed whereby to ~~define~~ an equal number of twists per foot in the lengths of formed cutting line is defined.

3. (Original) The assembly of claim 1 wherein said drive assembly comprises a plurality of drive cylinders, each of said cylinders engaging one of said dies, a plurality of gears, each of said gears being operatively connected to one of said drive cylinders and at least one of the other gears, and a drive motor operatively connected to one of said gears for synchronously rotating all of said gears whereby said dies are caused to undergo synchronous rotation.

4. (Original) The assembly of claim 3 wherein each of said dies has elongated body portion defining a drive engagement surface, said die hole configuration being disposed in a lower extended end of said body portion and wherein each of said drive cylinders defines an interior drive engagement surface abutting a drive engagement surface on one of said dies so that synchronous rotation of said drive cylinders effects synchronous rotation of said dies.

5. (Original) The assembly of claim 1 wherein said die hole configuration in each of said dies comprises a pair of circular holes of equal diameter spaced apart a distance less than said diameter.

6. (Original) The assembly of claim 1 wherein said die hole configuration in each of said dies comprises a plurality of holes connected together at adjacent edge portions.

7. (Original) The assembly of claim 1 wherein said die hole configuration in each of said dies comprises a single hole having the configuration of the cross-section of an oblate spheroid.

8. (Original) The assembly of claim 1 wherein said die hole configuration in each of said dies comprises a pair of holes connected together by a thin web portion.

9. (Original) The assembly of claim 1 wherein the die hole configuration in at least one of said dies is different from the die hole configuration in at least one of the other of said dies.

10. (Currently Amended) The assembly of claim 5 wherein said drive assembly is operatively connected to said dies so as to effect synchronous rotation ~~synchronously rotates~~ of each of said dies at said ~~predetermined~~ speed whereby to ~~define~~ an equal number of twists per foot in the lengths of formed cutting line is defined.

11. (Currently Amended) The assembly of claim 6 wherein said drive assembly is operatively connected to said dies so as to effect synchronous rotation ~~synchronously rotates~~ of each of said dies at said ~~predetermined~~ speed whereby to ~~define~~ an equal number of twists per foot in the lengths of formed cutting line is ~~defined~~.

12. (Currently Amended) The assembly of claim 7 wherein said drive assembly is operatively connected to said dies so as to effect synchronous rotation ~~synchronously rotates~~ of each of said dies at said ~~predetermined~~ speed whereby to ~~define~~ an equal number of twists per foot in the lengths of formed cutting line is ~~defined~~.

13. (Currently Amended) The assembly of claim 8 wherein said drive assembly is operatively connected to said dies so as to effect synchronous rotation ~~synchronously rotates~~ of each of said dies at said ~~predetermined~~ speed whereby to ~~define~~ an equal number of twists per foot in the lengths of formed cutting line is ~~defined~~.

14. (Currently Amended) The assembly of claim 9 wherein said drive assembly is operatively connected to said dies so as to effect synchronous rotation ~~synchronously rotates~~ of each of said dies at said ~~predetermined~~ speed whereby to ~~define~~ an equal number of twists per foot in the lengths of formed cutting line is ~~defined~~.

15. (Currently Amended) The assembly of claim 1 wherein said drive assembly comprises a planetary gear assembly operatively connected to said extrusion dies for synchronously rotating each of said dies at said ~~predetermined~~ speed.

16. (Original) The assembly of claim 15 wherein said die hole configuration in each of said dies comprises a pair of circular holes of equal diameter spaced apart a distance less than said diameter.

17. (Original) The assembly of claim 15 wherein said die hole configuration in each of said dies comprises a pair of holes connected together at adjacent edge portions.

18. (Original) The assembly of claim 15 wherein said die hole configuration in each of said dies comprises a pair of holes connected together by a thin web portion.

19. (Original) The assembly of claim 15 wherein the die hole configuration in at least one of said dies is different from the die hole configuration in at least one of the other of said dies.

20. (Currently Amended) An assembly for use in continuously forming a plurality of lengths of flexible noise attenuating cutting line for use in rotary vegetation trimmers comprised of one or more twisted ~~monofilament polymer~~ strands of monofilament, said assembly comprising: a housing having a chamber therein; a channel disposed within said housing above said chamber adapted for fluid communication with a source of molten monofilament ~~polymer material~~ for directing said ~~material~~ molten monofilament to said chamber; a breaker plate disposed in said chamber, said plate defining an inclined inner portion and a substantially planar outer portion, said inner portion directing molten ~~material~~ monofilament from said channel onto said outer portion; a plurality of extrusion dies disposed in said outer portion of said breaker plate, each of said dies defines defining a die hole configuration in the lower end thereof for the extrusion of one or more strands of molten monofilament ~~polymer strands~~ therethrough; and a drive assembly for rotating each of said dies at a ~~predetermined~~ speed to effect a twisting of the molten strand or strands of ~~polymer material~~ monofilament being extruded through each of said dies.

21. (Currently Amended) The assembly of claim 20 wherein said drive assembly is operatively connected to said dies so as to effect synchronous rotation ~~synchronously rotates~~ of each of said dies at said ~~predetermined~~ speed whereby to

~~define~~ an equal number of twists per foot in the lengths of formed cutting line is defined.

22. (Original) The assembly of claim 20 wherein said drive assembly comprises a plurality of drive cylinders, each of said cylinders engaging one of said dies, a plurality of gears, each of said gears being operatively connected to one of said drive cylinders and at least one of the other gears, and a drive motor operatively connected to one of said gears for synchronously rotating all of said gears whereby said dies are caused to undergo synchronous rotation.

23. (Original) The assembly of claim 22 wherein each of said dies has elongated body portion defining a drive engagement surface, said die hole configuration being disposed in a lower extended end of said body portion and wherein each of said drive cylinders defines an interior drive engagement surface abutting a drive engagement surface on one of said dies so that synchronous rotation of said drive cylinders effects synchronous rotation of said dies.

24. (Original) The assembly of claim 20 wherein said die hole configuration in each of said dies comprises a pair of circular holes of equal diameter spaced apart a distance less than said diameter.

25. (Currently Amended) The assembly of claim 24 wherein said drive assembly is operatively connected to said dies so as to effect synchronous rotation ~~synchronously rotates~~ of each of said dies at said ~~predetermined~~ speed whereby to

define an equal number of twists per foot in the lengths of formed cutting line is defined.

26. (Original) The assembly of claim 20 wherein said die hole configuration in each of said dies comprises a single hole having the configuration of the cross-section of an oblate spheroid.

27. (Currently Amended) The assembly of claim 26 wherein said drive assembly is operatively connected to said dies so as to effect synchronous rotation ~~synchronously rotates~~ of each of said dies at said ~~predetermined~~ speed whereby to ~~define~~ an equal number of twists per foot in the lengths of formed cutting line is defined.

28. (Currently Amended) An assembly for use in continuously forming a plurality of lengths of flexible noise attenuating cutting line for use in rotary vegetation trimmers comprised of one or more twisted ~~monofilament polymer~~ strands of monofilament, said assembly comprising: a housing; a plurality of extrusion dies disposed in said housing, each of said dies defining a die hole configuration in the lower end thereof for the extrusion of one or more strands of molten monofilament polymer strands therethrough; a fluid flow pathway disposed within said housing adapted for fluid communication with a source of molten monofilament ~~polymer material~~ for directing said ~~material~~ molten monofilament onto said dies; and a drive assembly for rotating each of said dies at a



~~predetermined~~ speed to effect a twisting of the molten strand or strands of ~~polymer material~~ monofilament being extruded through each of said dies.

29. (Currently Amended) The assembly of claim 28 wherein said drive assembly is operatively connected to said dies so as to effect synchronous rotation ~~synchronously rotates~~ of each of said dies at said ~~predetermined~~ speed whereby to ~~define~~ an equal number of twists per foot in the lengths of formed cutting line is defined.

30. (Original) The assembly of claim 28 wherein said drive assembly comprises a plurality of drive cylinders, each of said cylinders engaging one of said dies, a plurality of gears, each of said gears being operatively connected to one of said drive cylinders and at least one of the other gears, and a drive motor operatively connected to one of said gears for synchronously rotating all of said gears whereby said dies are caused to undergo synchronous rotation.

31. (Original) The assembly of claim 30 wherein each of said dies has elongated body portion defining a drive engagement surface, said die hole configuration being disposed in a lower extended end of said body portion and wherein each of said drive cylinders defines an interior drive engagement surface abutting a drive engagement surface on one of said dies so that synchronous rotation of said drive cylinders effects synchronous rotation of said dies.

32. (Original) The assembly of claim 28 wherein said die hole configuration in each of said dies comprises a pair of circular holes of equal diameter spaced apart a distance less than said diameter.

33. (Original) The assembly of claim 28 wherein said die hole configuration in each of said dies comprises a pair of holes connected together at adjacent edge portions.

34. (Original) The assembly of claim 28 wherein said die hole configuration in each of said dies comprises a plurality of holes connected together at adjacent edge portions.

35. (Original) The assembly of claim 28 wherein said die hole configuration in each of said dies comprises a single hole having the configuration of the cross-section of an oblate spheroid.

36. (Original) The assembly of claim 29 wherein said die hole configuration in each of said dies comprises a pair of circular holes of equal diameter spaced apart a distance less than said diameter.

37. (Original) The assembly of claim 29 wherein said die hole configuration in each of said dies comprises a single hole having the configuration of the cross-section of an oblate spheroid.